

## Inside Screw Gate Valves

Inside screw gate valves are used underground with indicator posts attached or as roadway box valves (curb box installation). FM Approved valves are available with a variety of end connections as indicated in the listings.

Valves having Ring-Tite, Fluid-Tite or Tyton-Joint connections should be anchored in place during installation. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models SFL-NRS-200-F, SFL-NRS-300-F, SFL-NRS-200-G, SFL-NRS-300-GG, SFL-NRS-200-FG, SFL-NRS-300-FG

Resilient Seated Gate Valves. 2 through 12 in. NPS. Available with the following end connections

<i>Model</i>	<i>Size, in. (mm)</i>	<i>Rated Working Pressure, psi (kPa)</i>	<i>End Connection</i>
SFL-NRS-200-F	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	200 (1380)	Flange x Flange
SFL-NRS-300-F	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	300 (2070)	Flange x Flange
SFL-NRS-200-G	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	200 (1380)	Groove x Groove
SFL-NRS-300-GG	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	300 (2070)	Groove x Groove
SFL-NRS-200-FG	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	200 (1380)	Groove x Flange
SFL-NRS-300-FG	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	300 (2070)	Groove x Flange

<b>Company Name:</b>	Sanflo Technologies
<b>Company Address:</b>	401 E. 1st Street #1868-0268, Sanford, Florida 32772, USA
<b>Company Website:</b>	Not Available
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved
<b>Class of Work:</b>	1130-OS&Y and NRS Gate Valves