

## Outside Screw and Yoke Gate Valves

Outside screw and yoke gate valves are recommended for service indoors and in pits outdoors. They are not recommended for throttling service. The stem indicates at a glance whether or not the valve is open. Smaller sizes, 3/4 through 2 in. NPS inclusive, are of bronze. Large sizes, 2 1/2 through 14 in. NPS inclusive, are of iron, bronze mounted. One manufacturer makes valves of bronze up through the 3 in. size. Unless otherwise noted in the listing, these valves have 175 psi (1205 kPa) rated working pressure.

### Models SFL-OSY-200-F, SFL-OSY-300-F, SFL-OSY-200-G, SFL-OSY-300-GG, SFL-OSY-200-FG, SFL-OSY-300-FG

**Resilient Seated Gate Valves. 2 through 16 in. NPS. Available with the following end connections.**

<i>Model</i>	<i>Size, in. (mm)</i>	<i>Rated Working Pressure, psi (kPa)</i>	<i>End Connection</i>
SFL-OSY-200F	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12, 14, 16 80, 100, 125, 150, 200, 250, 300, 350, 400)	200 (1380)	Flange x Flange
SFL-OSY-300-F	2, 2 1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	300 (2070)	Flange x Flange
SFL-OSY-200-G	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	200 (1380)	Groove x Groove
SFL-OSY-300-GG	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	300 (2070)	Groove x Groove
SFL-OSY-200-FG	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	200 (1380)	Groove x Flange
SFL-OSY-300-FG	2, 2-1/2, 3, 4, 5, 6, 8, 10, 12 (50, 65, 80, 100, 125, 150, 200, 250, 300)	300 (2070)	Groove x Flange

<b>Company Name:</b>	Sanflo Technologies
<b>Company Address:</b>	401 E. 1st Street #1868-0268, Sanford, Florida 32772, USA
<b>Company Website:</b>	Not Available
<b>New/Updated Product Listing:</b>	No
<b>Listing Country:</b>	United States of America
<b>Certification Type:</b>	FM Approved
<b>Class of Work:</b>	1130-OS&Y and NRS Gate Valves