



COMMERCIAL PRESSURE GAUGE: GLYCERIN FILLED

**SFL-GAU-GLYC-4 WITH ¼" CONNECTION /
SFL-GAU-GLYC-4B WITH ½" CONNECTION**

GENERAL DESCRIPTION

Sanflo's Commercial Pressure Gauge is designed to meet both EN837-1 and ASME B40.100, ensuring accuracy and long term performance. This high quality pressure gauge is designed for compressors, hydraulic systems, and many other OEM applications – making easy to retrofit. Dampening with glycerin fill.

KEY TECHNICAL FEATURES / PRODUCT SPECS

<p>Approvals: RoHS (EU Directives 2011/65/EU and 2015/863) PED (2014/68/EU); CRN; IP 66 rating NEMA 4 for water and dust ingress</p>	<p>Case: 304 SS Corrosion Resistant Stainless Steel Case Window: Polycarbonate Glass Ring: 304 SS, crimped</p>
<p>Accuracy: ±1% of span per EN837-1</p>	<p>Dial and Pointer: Black</p>
<p>Dampening: Glycerin Filled</p>	<p>Movement: Brass</p>
<p>Dial Size: 100mm (4") Connection: ¼" OR ½" NPT Male</p>	<p>RANGES: Vacuum, compound, 0 - 500 psi, bar, kPa, MPa, kg/cm</p>
<p>WORKING PRESSURE Steady: 75% full-scale value; Fluctuating: 80% full-scale value; Short Time: full-scale value</p>	<p>MIN/MAX TEMP LIMITS GLYCERIN MODEL AMBIENT: 20°F to 158°F (-7°C to 70°C) PROCESS: -4°F to 158°F (-20°C to 70°C) STORAGE: 40°F to 158°F(-40°C to 70°C)</p>