




# WALL INDICATOR POST

**MODEL: SFL-IPW**



**SIZES 2.5" TO 12"**

## GENERAL DESCRIPTION

Sanflo Wall Indicator Posts are designed for use in fire protection services and are installed in a horizontal position. They are connected to a buried SANFLO NRS GATE VALVE located behind the wall, and allow the user to visually inspect if the NRS valve is in the ON (OPEN) or OFF (SHUT) position. The indicator post operates the NRS Gate Valve (control valve) in an automatic sprinkler system.

## SIZES

Universal size fits SANFLO NRS GATE VALVES 4" to 12"

### KEY TECHNICAL FEATURES

Testing: UL 789, ULC/ORD-C798 & FM CLASS 110	Hand wheel operated
Approvals: UL, ULC and FM	Coating: fusion bonded epoxy interior And exterior conforming to AWWA C550
Comes in two factory configurations: open left or open right. Opening direction can also be changed in the field	Comes with a 12 inch outer diameter flange to easily mount on the wall

## ON-SITE FIELD ADJUSTMENT INSTRUCTIONS:

Remove the top cap. Depending on NRS valve size, set accordingly the OPEN and SHUT targets. Replace the top cap.

## CARE AND MAINTENANCE

No regular maintenance is required, however it is advisable to annually inspect and verify proper operation. The frequency of testing, inspections, and/or maintenance is the sole responsibility of the end user. Only qualified fire protection integrators should perform any required maintenance involving the valve.

## ORDERING INFORMATION:

Specify model **SFL-IPW**

## INSTALLATION

Carefully follow instructions on the installation sheet included with the valve.



**WALL INDICATOR POST**  
**MODEL: SFL-IPW**

<b>MATERIAL SPECIFICATIONS</b>		
<b>ITEM</b>	<b>PART</b>	<b>MATERIAL &amp; SPEC</b>
1	Hand wheel	Ductile iron, ASTM A536 gr. 65-45-12
2	Eye bolt	Carbon steel, ASTM A307B
3	Hex nut	Carbon steel, ASTM A307B
4	Washer	Carbon steel, ASTM A570 GR. 33
5	Hex cap screw	Carbon steel, ASTM A307B
6	Cotter pin	Stainless Steel, AISI 304
7	Square nut	Carbon steel, ASTM A307B
8	Snap ring	Stainless Steel, AISI 1066
9	Cover	Carbon steel, ASTM A307B
10	Hex nut	Cast iron, ASTM A126 class B
11	Stem	Carbon steel, AISI 1045
12	Body	Cast iron, ASTM A126 class B

<b>MATERIAL SPECIFICATIONS</b>		
	<b>PART</b>	<b>MATERIAL &amp; SPEC</b>
13	Target carrier nut	Bronze, ASTM B62 C83600 Stainless Steel, AISI 304
14	Hex cap screw	Carbon steel, ASTM A307B
15	Hex nut	Carbon steel, ASTM A307B
16	Target	Cast Aluminum
17	Window glass	Plexi-glass
18	Gasket	PTFE
19	Operating nut	Bronze, ASTM B62 C83600 Stainless Steel, AISI 304
20	Crane coupling	Ductile iron, ASTM A536 gr. 65-45-12
21	Plug	Malleable iron

**SANFLO PRODUCT WARRANTY**

One (1) year from original sale date. Sanflo guarantees to repair or replace any products deemed to be defective in material or fabrication. Visit our website for full warranty details.