

Valves | Indicating Valves (Butterfly or Valve Type) | **Indicating Valves, Butterfly or Ball Type**

Models SFL-BV-300-W, SFL-BV-300-WX, SFL-BV-300-G, SFL-BV-300-GX

Product Description

Model No	Description	Valve Size		Rated Working Pressure		Remarks
		in	(mm)	psi	(kPa)	
SFL-BV-300-W	Butterfly Valve, Wafer by Wafer End Connections	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
SFL-BV-300-WX	Butterfly Valve, Wafer by Wafer End Connections	2, 10, 12	(50, 250, 300)	300	(2065)	a, b, c
SFL-BV-300-G	Butterfly Valve, Groove x Groove End Connections	2 1/2, 3, 4, 5, 6, 8	(65, 80, 100, 125, 150, 200)	300	(2065)	a, b, c
SFL-BV-300-GX	Butterfly Valve, Groove x Groove End Connections	2, 10, 12	(50, 250, 300)	300	(2065)	a, b, c

- Remarks:**
- a. Available with or without supervisory switches.
 - b. FM Approved for indoor and outdoor service.
 - c. FM Approved for aboveground installations only.

Details

Category	Indicating Valves, Butterfly or Ball Type
Class of Work	1112 - Indicating Valves
Approval Standard	FM 1112 - Indicating Valves (Butterfly or Ball Type)
Certification Type	FM Approved

Company

Sanflo Technologies
411 W. 1st Street, #1005, Sanford
, Florida 32771
United States of America
<http://sanflotek.com>

 Approvals

Listing Country

United States of America